

Related Products: Multi-holder

Series TMA

- Can be used to secure the KE□ series exhaust valve with One-touch fitting.
- One-touch fitting can also be secured.
Union tee: KQT,
Elbow: KQL,
Straight: KQH
- Depending on the number of holders required, they can be separated as desired. (Align the cutter with the cutting groove and cut the holder.)





Specifications

Ambient temperature	-20 to 60°C (No freezing)
Material	Flame resistant polypropylene (Equivalent to UL-94 standard V-0)
Color	Black

Model

Model	Stations	Applicable exhaust valve	Applicable One-touch fitting		
			Union tee	Union elbow	Straight union
TMA-06	8	KEA06	KQT06-00	KQL06-00	KQH06-00
		KEB06			
TMA-08	8	KEA08	KQT08-00	KQL08-00	KQH08-00
		KEB08			
		KEC-02			
TMA-10	6	KEA10	KQT10-00	KQL10-00	KQH10-00
		KEB10			
TMA-12	6	KEA12	KQT12-00	KQL12-00	KQH12-00
		KEB12			
		KEC-03			

Dimensions: Multi-holder



Applicable tubing O.D. (mm)	Model	P	L	W	H ₁	H ₂	Q
6	TMA-06	19	151	28	11.4	17.9	18.6
8	TMA-08	21.7	172.5	31.8	12.6	20.3	18.6
10	TMA-10	25.4	151.2	35	15	24.3	22
12	TMA-12	28.1	167.3	37	16.2	26.7	22

K□

M□

H□

KK

D□

MS

LQ

MQR

T□